KRAL

کرال صنعت مرند

KRAL SANAT MARAND

تریلر تیغه کانتینر بر سه محور

CONTAINER CARRIER 3 AXLEX

Container Carrier 3 Axles (TK534-L)

Dimensions	Length : 12,140 mm | Width : 2,500 mm
Max. Payload	29 tons | Ability to carry 1x40' / 2x20' containers up to totally 28.5 tons | Ability to carry a 20' container in the middle (max. 24 tons)
Weight	4 ton-Approximately
Chassis	Chassis & components from St. 52-3 / QST 380 / S 500 | Automatic CO2 welding technology / Merkle, Germany | Main I beams with standard flat bar | All steel stamping parts are assembled using special fixture and automatic devices
Axle	3 x 9 tons SAF® | Front axle with automatic lifting capability
Suspension	Air suspension with special shock absorbers | Lowering and rising of trailer height
Tire/Rim	6 x Radial tires 385/65 R22.5 | 6 x Single rims 11.75 x R22.5"
Landing Gear	Two mechanically operated landing legs 24 tons dynamic capacity & 50 tons static capacity Operated from right side
King Pin	2" dia. (162 KN) with coupling according to SAE standard with special bolster plate | Corner dimension :2040 mm
Braking System	**Knorr ,WABCO, HALDEX** 2S/2M, Disk according to ECE-R13 standard. | Dual circuit pneumatic with automatic load sensing valves | Two double acting diaphragm brake chambers (2 rear axles) EBS incl. ABS & RSP (Roll Stability Program) / Emergency valve / Parking brake/Reset-to-Ride height function
Electrical System	7 & 15 Poles quick release connector with 24 volts rear and side lights plus LED alarming system According to UNECE regulation R48
Painting	Shot blasted according to SA 2.5 / Epoxy sub-coat Final polyurethane coating as per customer requirement/Color According to RAL system
Accessories	Rear bumper / Rear under-run protection according to UNECE Regulation / Rubber shock absorbers (rear) / 12 x Container locks 2 x Carrier hooks / 6 x Semi-circle mud guards / 2 x Rear rain flap spray (suppression system according to UNECE Regulation) / 2 x Wheel chocks and holders / Fire extinguisher box / Spare wheel carrier with clamp mechanism / 2 x Tool boxes (1.22 m with two different models)/ Side protection and Reflective outline marking on side/rear according to UNECE Regulation.
Options	125 L Stainless steel water tank / Spare tire & rim / Tire-pressure monitoring system (TPMS)

Certified by INSO (Iran National Standards Organization) & European Commission

تریلر تیغه کانتینر بر سه محور (TK534-L)

ابعاد	طول (میلیمتر): ۱۲،۱۴۰ | عرض (میلیمتر): ۲،۵۰۰
ظرفیت	۲۹ تن | قابلیت حمل یک عدد کانتینر ۴۰ فوت یا دو عدد ۲۰ فوت جمعاً تا ۲۸.۵ تن | قابلیت حمل یک عدد کانتینر ۲۰ فوت در وسط حداکثر تا ۲۴ تن
وزن	حدودا ۴ تن
شاسی	شاسی و قطعات از فولاد با استحکام بالا St. 52-3/ QST 380 / S 500 | جوش آرگون اتوماتیک با فن آوری مرکله آلمان | تیرهای اصلی با تسمه استاندارد | مقاطع پرسی فولادی مونتاژ شده در فیکسچر مخصوص و دستگاه های خودکار
محور	سه عدد محور ۹ تن SAF | محور جلو دارای بالابر اتوماتیک با بوستر تک
زیربندی	سیستم تعلیق بادی بالنی و کمک فنر مخصوص | قابلیت تنظیم ارتفاع تریلر
رینگ و لاستیک	۶ حلقه لاستیک سایز 385/65 R22.5 | ۶ عدد رینگ یک تکه سایز 11.75 x R22.5"
پایه توقف	دو سرعته با ظرفیت دینامیکی ۲۴ تن و ظرفیت استاتیکی ۵۰ تن | سمت کمک راننده
میل ریش	۲ اینچ با قدرت ۱۶۲ کیلونیوتن به همراه فلنج مربوطه مطابق استاندارد SAE با ضخامت صفحه ریش مخصوص | شعاع چرخش ۲۰۴۰ میلی متر
سیستم ترمز	دیسکی HALDEX , WABCO, Knorr 2S/2M بر طبق استاندارد ECE-R13 | دو مسیر باد اصلی برای تمام چرخها همراه شیر سبک و سنگین اتوماتیک بار | ۲ عدد بوستر جفت برای دو محور عقب سیستم EBS (ترمز ضد قفل و سامانه ضدواژگونیRSP) / ترمز اضطراری / سیستم قفل پارک/سیستم تنظیم خودکار ارتفاع
سیستم برق	دارای کلید ۷ و ۱۵ پل با خط برق ۲۴ ولت چراغهای عقب و بغل / سیستم هشدار از نوع LED طبق استاندارد جهانی R۴۸
رنگ شاسی	شات شده مطابق استاندارد SA 2.5 / زیرسازی با ضد زنگ اپوکسی رنگ نهایی پلی اورتان طبق نظر مشتری /بر اساس سیستم کد گذاری RAL
متعلقات	سپر عقب / سپر محافظ عقب بر طبق استاندارد جهانی / ضربه گیر غلتکی عقب / ۱۲ عدد قفل کانتینر ۲ عدد قلاب حمل / ۶ عدد گلگیر نیم دایره / ۲ عدد گل پخش کن عقب با شلگیر بر طبق استاندارد جهانی / ۲ عدد دنده پنج و نگهدارنده /براکت کپسول آتش نشانی / زاپاس بند مستکم کلمپی / ۲ عدد جعبه ابزار ۱.۲۲ متری با دو مدل مختلف / گارد بغل، شبرنگ مخصوص نصب شده در کنار / عقب بر طبق استاندارد جهانی
قابل سفارش	تانک آب استیل ۱۲۵ لیتری / رینگ و لاستیک زاپاس / سیستم نشان گر باد تایر

دارای مجوز از سازمان ملی استاندارد و کنوانسیون اروپا



Certificate Control Quality &Testing

(۰۲۱) ۸۶۰ ۸۸ ۳۱۰ | (۰۲۱) ۸۶۰ ۸۵ ۸۴۰
info@kralsanat.com
www.kralsanat.com
تهران، جردن، خیابان نلسون ماندلا، کوچه بابک بهرامی، پلاک ۳۷، طبقه دوم