تریلر تیغه تانکر سه محور
TANK CARRIER 3 AXLES
KRAL
کرال صنعت مرند
KRAL SANAT MARAND

Tank Carrier 3 Axles (TG530-A)

Dimensions	Length: 11,000 mm | Width: 2,500 mm
Max. Payload	28 tons
Weight	3,700 Kg -Approximately
Chassis	Chassis & components from St. 52-3 / QST 380 / S 500 | Automatic CO2 welding technology / Merkle, Germany Main I beams with standard flat bar | All steel stamping parts are assembled using special fixture
Axle	3 x 9 tons SAF® | Front axle with automatic lifting capability
Suspension	Air suspension with special shock absorbers | Lowering and rising of trailer height
Tire/Rim	6 x Radial tires 385/65 R22.5 | 6 x Single rims 11.75 x R22.5"
Landing Gear	2 mechanically operated landing legs 24 tons dynamic capacity & 50 tons static capacity | Operated from right side.
King Pin	2" dia. (162 KN) with coupling according to SAE standard with special bolster plate according to UNECE regulation ECE-R55 standard | Corner dimension :2040 mm
Braking System	**Knorr ,WABCO,HALDEX** 2S/2M, Disk/ according to ECE-R13 standard. Dual circuit pneumatic with automatic load sensing valves | Two double acting diaphragm brake chambers (2 rear axles) | EBS incl. ABS & RSP (Roll Stability Program) / Emergency valve / Parking brake/Reset-to-Ride height function.
Electrical System	7 & 15 Poles quick release connector with 24 volts rear and side lights plus LED alarming system According to UNECE regulation R48
Painting	Shot blasted according to SA 2.5 / Epoxy sub-coat Final polyurethane coating as per customer requirement/Color According to RAL system
Accessories	Rear guard protection / Rear under-run protection according to UNECE Regulation ECE-R73 / Rubber Buffer absorbers (rear) / 2 x Heavy D Ring /6 x Semi-circle mud guards / 2 x Rear Spray suppression system according to UNECE Regulation-EU 109/2011) / 2 x Wheel chocks with holders / Fire extinguisher bracket/Spare wheel carrier with clamp mechanism / 1 x Tool box (1 m) /Side protection and Reflective outline marking according to UNECE Regulation
Options	125 L Stainless steel water tank / Spare tire & rim / Tire-pressure monitoring system (TPMS)

Certified by INSO (Iran National Standards Organization) & European Commission

تریلر تیغه تانکر سه محور (TG530-A)

ابعاد	طول (میلیمتر): ۱۱،۰۰۰ | عرض (میلیمتر): ۲،۵۰۰
ظرفیت	۲۸ تن
وزن	۳،۷۰۰ کیلو گرم-تقریبی
شاسی	شاسی و قطعات از فولاد با استحکام بالا St. 52-3/ QST 380 / S 500 | جوش آرگون اتوماتیك با فن آوری مرکله آلمان تیرهای اصلی با تسمه استاندارد | مقاطع پرسی فولادی مونتاژ شده در فیکسچر مخصوص
محور	سه عدد محور 9 تن SAF | محور جلو دارای بالابر اتوماتیك با بوستر تك
زیربندی	سیستم تعلیق بادی بالنی و کمك فنر مخصوص | قابلیت تنظیم ارتفاع تریلر
رینگ و لاستیك	6 حلقه لاستیك سایز 385/65 R22.5 | ۶ عدد رینگ یك تکه سایز "11.75 x R22.5
پایه توقف	دو سرعته با ظرفیت دینامیکی ۲۴ تن و ظرفیت استاتیکی 50 تن | سمت کمك راننده
میل ریش	۲ اینچ با قدرت ۱۶۲ کیلونیوتن به همراه فلنج مربوطه مطابق استاندارد SAE با ضخامت صفحه ریش مخصوص شعاع چرخش ۲۰۴۰ میلی متر
سیستم ترمز	دیسکی HALDEX , WABCO, Knorr 2S/2M بر طبق استاندارد ECE-R13 | دو مسیر باد اصلی برای تمام چرخها همراه شیر سبك و سنگین اتوماتیك بار | ۲ عدد بوستر جفت برای دو محور عقب | سیستم EBS (ترمز ضد قفل و سامانه ضدواژگونی RSP) / ترمز اضطراری / سیستم قفل پارك/سیستم تنظیم خودکار ارتفاع
سیستم برق	دارای کلید ۷ و ۱۵ پل با خط برق ۲۴ ولت چراغهای عقب و بغل / سیستم هشدار از نوع LED طبق استاندارد جهانی R48
رنگ شاسی	شات شده مطابق استاندارد SA 2.5 / زیرسازی با ضد زنگ اپوکسی رنگ نهایی پلی اورتان طبق نظر مشتری / بر اساس سیستم کد گذاری RAL
متعلقات	سپر عقب / سپر محافظ عقب بر طبق استاندارد جهانی ECE-R73 / ضربه گیر غلتکی عقب / 2 عدد قلاب حمل ۶ عدد گلگیر نیم دایره / ۲ عدد گل پخش کن عقب با شلگیر بر طبق استاندارد جهانی EU 109/2011 / ۲ عدد دنده پنج و نگهدارنده / براکت کپسول آتش نشانی/زاپاس بند مستحکم کلمپی / یك عدد جعبه ابزار ۱ متری / گارد بغل ، شبرنگ مخصوص بر طبق استاندارد جهانی
قابل سفارش	تانك آب استیل ۱۲۵ لیتری / رینگ و لاستیك زاپاس / سیستم نشان گر باد تایر

دارای مجوز از سازمان ملی استاندارد و کنوانسیون اروپا



Certificate Control Quality &Testing

(۰۲۱) ۸۶۰ ۸۸ ۳۱۰ | (۰۲۱) ۸۶۰ ۸۵ ۸۴۰
info@kralsanat.com
www.kralsanat.com
تهران، جردن، خیابان نلسون ماندلا، کوچه بابک بهرامی، پلاک ۳۷، طبقه دوم